

Transient Voltage Suppressor

Version: A4 2022-05-27

Features

- IEC 61000-4-2(ESD)±30KV(air), ±30KV(contact)
- IEC61000-4-5(Lightning) 17A (8/20μS)
- IEC61000-4-4(EFT) 40A (5/50nS)
- 100 Watts peak pulse power (tp=8/20μS)
- Low clamping voltage
- Weight approx. 0.5 mg
- Small package: DFN1006
- Moisture sensitivity level: Level 1

Exterior



DFN1006-2L

Application information

- Portable instruments
- Desktops, Servers and Notebooks
- Cellular Phones
- MP3 Players
- Keypads, Side Keys
- USB2.0 Data Line Protection


Package (top view)



Agency Approvals

Icon	Description
RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003
	Mean lead free

Schematic



Part Number and Electrical Parameter

Part Number	I _{DRM} @V _{DRM}		V _{TR} ^① @I _{TR}		V _{SB} ^① @I _{SB}		V _c @I _{pp} ^②		V _c @I _{pp} ^②		Co ^③	
	μA	V	V	mA	V	mA	V	A	V	A	pF	
	MAX		MIN		MIN		MAX		MAX		TYP	MAX
BV-FA2.5UCB	0.1	2.5	2.8	1	2.6	50	5	1	10	10	3	5

Absolute maximum ratings measured at T= 25°C RH = 45%-75% (unless otherwise noted).

① V_{TR} is measured at I_{TR}=1mA, V_{SB} is measured at I_{SB}=50mA

② Surge Waveform: 8/20μS.

③ Off-state capacitance is measured in V_{DC}=0V, V_{RMS}=0.3V, f=1MHz

Transient Voltage Suppressor

Part Numbering System

BV FA 2.5 U C B
(1) (2) (3) (4) (5) (6)

- (1) Bencent Transient Voltage Suppressor
- (2) Package:DFN1006
- (3) Off-state Voltage: 2.5V
- (4) Low Capacitance
- (5) Bidirectional
- (6) Bencent intenal code


Mark

2V5Z



2V5Z: Part Number

V-I Curve

Parameters	Definition
V_C	Clamping voltage
I_{PP}	Surge waveform 8/20 μ s
V_{DRM}	Stand-off Voltage
V_{TR}	Trigger Voltage
V_{SB}	Snapback Voltage
I_{DRM}	Reverse Leakage Current
I_{TR}	Test current
I_{SB}	Test current
P_{PP}	Peak Pulse Power Dissipation



Typical Characteristics



Transient Voltage Suppressor

Version: A4 2022-05-27

Thermal Considerations


symbol	Parameter	Value	Unit
T_J	Operating Junction Temperature Range	-40 to +125	°C
T_S	Storage Temperature Range	-55 to +150	°C

Environmental Characteristics

Testing items	Technical standards
High temperature Reverse Bias Test	Temperature: $125 \pm 3^\circ\text{C}$ Bias= $80\%V_{\text{DRM}}$ Time:168H
High Temperature Life Test	Temperature: 150°C Time:168H
High-low Temperature Cycle test	Temperature: From -40°C to 125°C Dwell time : 30min,10~100cycles
High Temperature &High Humidity Test	Temperature: 85°C Humidity:85% Time:168H
Pressure cooker Test	Temperature: 121°C , 2atm. Humidity:100% Time:24H
Resistance of soldering heat	Temperature: $260 \pm 5^\circ\text{C}$ Time of dip soldering: 10s, 3times


Note: The above testing items can be specified by customer's special request

Product Dimensions



REF	mm	inch
A	0.30~0.55	0.012~0.022
A1	0~0.05	0.000~0.002
A3	0.125 REF	0.020REF
D	0.95~1.10	0.037~0.043
E	0.55~0.70	0.022~0.028
b	0.20~0.30	0.008~0.012
e	0.65BSC	0.026BSC
L	0.45~0.55	0.018~0.022

Recommended Soldering Pad




REF	mm	inch
A	0.35	0.014
B	0.60	0.024
C	0.35	0.014

Transient Voltage Suppressor


Version: A4 2022-05-27

Reflow Profile

Reflow Condition		Pb-Free assembly
Pre Heat	Temperature Min	150°C
	Temperature Max	200°C
	Time (min to max)	60 – 180 secs
Average ramp up rate (Liquid)		3°C/s max
Tamp (T _L) to peal		
T _s (max) to T _L - Ramp-up Rate		3°C/s max
Reflow	- Temperature (T _L) (Liquid)	217°C
	- Temperature (T _L)	60 – 150 secs
Peak Temperature (T _P)		260+0/-5 °C
Time within 5°C of actual peak Temperature (T _P)		30secs
Ramp-down Rate		6°C/s max
Time 25°C to peak Temperature (T _P)		8 mins max.
Do not exceed		260°C



Package Reel Information



REF	mm	inch
A	0.70+/-0.05	0.028+/-0.002
B	1.15+/-0.05	0.045+/-0.002
d	1.50+0.1/-0	0.059+0.004/-0
D	178.00+/-2.00	7.008+/-0.079
D1	55.00+/-3.00	2.165+/-0.118
D2	13.00+/-0.50	0.512+/-0.020
E	1.75+/-0.10	0.069+/-0.004
F	3.50+/-0.20	0.138+/-0.008
P	2.00+/-0.20	0.079+/-0.008
P0	4.00+/-0.20	0.157+/-0.008
P1	2.00+/-0.20	0.079+/-0.008
W	8.00+/-0.20	0.315+/-0.008
W1	9.50+/-1.00	0.374+/-0.039

OUTLINE	REEL (PCS)	PER CARTON (PCS)	REEL DIAMETERS (mm)	CARTON SIZE(mm)		
				L	W	H
TAPING	10,000	300,000	178	390	370	220